# 2 Glass Door Reach-In Refrigerator



BGM-49-SD

## **Features**

#### **Bottom Mounted Compressor**

The bottom mounted compressor allows for easy access while loading, unloading, maintenance and cleaning. Also due to the temperature difference between the bottom and the top of the room this compressor location is superior to the top mounted style.

#### 2 Anti-Fog Self Closing Sliding Doors

Fully insulated glass doors while providing clear visibility of products inside also helps keep energy costs down by not allowing as much cold air to escape the unit while opening.

#### 8 Adjustable Interior Shelves

The interior shelves sit on adjustable mounting brackets; accommodating for different sized products with shelf by shelf height adjustments.

#### Digital Temperature Controls

The LCD display allows for easy visual read out and temperature control.

#### 4 Casters

Including 2 pre-installed front locking casters for easy set up and moving during cleaning or maintenance.

#### **LED Lighting**

The light-emitting diode(LED) lighting provides high visibility for customer's viewing.

# Technical Data Plan View

#### Dimensions

Exterior Dimensions (Inches) Interior Dimensions (Inches) Packaging Dimensions (Inches) Capacity (cu. ft.)

**Gross Weight** 

52.4" x 31.5" x 79.3" 48.5" x 23.7" x 61.5" 54.3" x 33.5" x 82.7" 48 cu. ft. 425 lbs

#### Construction

**Exterior Material** Interior Material Door/Lid Material Insulation Material # of Sliding Doors Self Closing Door Lock Mounted # of Shelves

Shelf Material Shelf Load Capacity


52.4\*

Painted Aluminum Glass Door Cyclopentane

Painted steel

Yes No 4

Plastic coated steel 90 lbs



### Cooling

Temperature Range Refrigerant Maximum Ambient Temperature Rating Defrosting Temperature Display Temperature Controller **Cooling System** Compressor H/P

Digital Ventilated 1/3

31.5"

33° - 40° F

Automatic

R290

90° F

Yes

## Electrical

Voltage (v/Hz) 115/60 9.5 Amps Phase





25 ...

78.25"

# # #

Front View

79.3

NEMA 5-15P